



65-Y-066 DTM Cat Yellow M.G. Acrylic AD

Description:

An acrylic modified, fast dry alkyd designed for use in touch up applications. Also suited for painting small parts to provide both substrate protection and color coordination.

Reduction Rate/Mix Ratio:

Ready to spray as supplied. Acetone may be added to adjust the viscosity if necessary. Non exempt solvents may exceed VOC limitations

Product Information:

Color: Cat Yellow

Weight Per Gallon: 8.59±.3

Solids by Volume: 42.84±3 %

Solids By Weight: 53.70±3 %

VOC: < 3.50

VOC Note: <420 grams/liter. Contains 22% exempt solvent by volume

Gloss: 35-45 / 60 ° meter

Viscosity: 40-45" #2 Zahn Cup

pH Level: N/A

Pot Life: N/A

Recommended Application:

Spray as supplied. May also be loaded into aerosol cans for touch up applications. Substrate must be clean and free of rust, oil, and moisture. Painted surfaces should be scuffed or sanded before repainting.

Clean Up Solvent(s):

Xylene, Acetone(exempt)

Curing Schedule:

Air Dry, Tack Free: 1-2 hours

Dry Through: 16-24 hours

Bake, Flash Time: N/A

Bake Temp: N/A

Dwell Time: N/A

PMT: N/A

Theoretical Coverage @ 1.0 Mil: 687 sq. ft. / gallon

Recommended Dry Film Thickness:

1.2-1.5 mils

Performance:

Adhesion: 4B-5B ASTM D 3359*

Durability: Suitable for exterior applications

Flexibility: N/A

Hardness: B-HB pencil ASTM D 3363

Impact: N/A

MEK Rubs: N/A

Salt Spray: 200 hours ASTM B 117

Other: As tested on B-1000 CRS after one week air dry

Date: 08/28/13

Supersedes:

A Certificate of Analysis establishes specifications as a customer product requirement, otherwise these specifications are representative guidelines and may be modified on particular batches. The information and specifications stated here are for material currently offered, are subject to change without prior notice, and due to variations in user handling and application methods should not be relied upon without testing under user conditions. The supplier makes no warranty of any kind, express or implied, concerning this product or its use, either singly or in combination with other substances. User assumes all risks incident to its use. User must communicate to employees and customers all warnings that relate to the potential exposure to this product. The user assures that workplace and disposal practices are in compliance with laws, regulations and ordinances. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

1920 Leonard Avenue, P.O. Box 369004, Columbus, Ohio 43236-9004 - (614) 253-8511